

M-Tech Special Order



Pattern achieved by ordering pallets of three different colours

Premium Finish Face Mix Technology

The M-Tech paver is manufactured on the pallet in a machine lay pattern. M-Tech is designed to accommodate heavy commercial traffic with its physical characteristics that include an enhanced interlock system. The enhanced interlock system is accomplished with multiple spacer tabs around all the edges of the paver, ensuring a robust vertical interlock. Helpful in areas with highly variable traffic loads and constant turning.

RECOMMENDED APPLICATIONS



Parking Lots 4.5" x 9" x 3-1/8"



Vehicular Traffic



Heavy Traffic 4.5" x 9" x 3-1/8"

COLOURS:



Natural



Midnight Black



Winter Sky

AVAILABLE SIZES:



6" x 12'

BLOCK SPECIFICATION:



Size (in)	Pieces per sq.ft.	Sq.ft. per Pallet	Shipping Weight	PCS / Pallet
6" x 12" x 5-15/16" 151mm x 304mm x 100mm	2	63	1433kg / 3020lbs	126


All sizes including 3 mm Spacer Bars



INSTALLATION INSTRUCTIONS:


Permeable Installation

FULL EXFILTRATION



- 1 Pave
- 2 Joint filling material ASTM No 10 (CSA 2–3mm) aggregate
- **3** Bedding course 1 1/5" to 2" (40 to 50 mm) ASTM No 8 (CSA 2.5–10mm) aggregate
- 4 Base course 4" (100mm) ASTM No 57 (CSA 5–28mm) aggregate foundation thickness
- 5 Subbase course ASTM No 2 (CSA 40-80mm) aggregate
- 6 Geotextile (optional)
- 7 Subgrade
- 8 Concrete Edge

Sand Set Installation



- 1 Pave
- 2 Sand joint fill
- 3 Bedding Sand 1"
- 4 Extra width equal to foundation thickness
- 5 Lawn
- 6 Plastic edge or other type of edge restraint
- 7 Nail
- 8 Geotextile (optional)
- 9 Compacted aggregate base with 34" minus material
- 10 Subgrade