

Urban

Premium Finish Face Mix Technology



Photo courtesy of Ocean Park Landscaping & Stone

6"x12" Natural

The new trend in Architectural Hardscape. Urban pavers have no chamfer which gives this distinctive look.



INDIVIDUAL SIZES:





6" x 9"

6" x 12

Size (in)	Pieces per sq.ft.	Sq.ft. per Pallet	Shipping Weight	PCS / Pallet
6" x 9" x 2-3/8" 151mm x 228mm x 60mm	2.67	101.25	1329kg / 2930lbs	270
6" x 12" x 2-3/8" 151mm x 304mm x 60mm	2	108	1361kg / 3000lbs	216

All sizes including 3 mm Spacer Bars



Please note, the lack of a chamfer requires installers to handle Urban pavers with more care than typical pavers.

RECOMMENDED APPLICATIONS



Patios



Walkways







Natural Charcoal










Installation Instructions:


Permeable Installation

FULL EXFILTRATION



- 1 Paver
- 2 Joint filling material ASTM No 10 (CSA 2-3mm) aggregate
- **3** Bedding course 1 1/5" to 2" (40 to 50 mm) ASTM No 8 (CSA 2.5–10mm) aggregate
- 4 Base course 4" (100mm) ASTM No 57 (CSA 5–28mm) aggregate foundation thickness
- 5 Subbase course ASTM No 2 (CSA 40-80mm) aggregate
- 6 Geotextile (optional)
- 7 Subgrade
- 8 Concrete Edge

Sand Set Installation



- 1 Paver
- 2 Sand joint fill
- 3 Bedding Sand 1"
- 4 Extra width equal to foundation thickness
- 5 Lawn
- 6 Plastic edge or other type of edge restraint
- 7 Nail
- 8 Geotextile (optional)
- 9 Compacted aggregate base with 3/4" minus material
- 10 Subgrade



All our pavers meet the H-20/H-S20 loading requirements. This determination allows for an occasional heavy vehicle such as a fire truck driving on the pavers. Specific site requirements will determine the appropriate paver usage. For example, heavily trafficked areas require more robust pavers installed in specific laying patterns.



Scan QR code for more information